



112-132 HP

# MF 6700

Designed from the ground up.  
Performance like no other global tractor.  
Rugged, dependable, easy to  
operate and maintain.



**FROM MASSEY FERGUSON**

# Specifications

|  | MF 6711                                     | MF 6712            | MF 6713            |          |
|--|---|--------------------|--------------------|----------|
| <b>Engine Performance</b>                              |   |                    |                    |          |
| Engine Power   | ISO hp (kW)                                 | 112 (83)           | 122 (91)           | 132 (98) |
| Max Torque   | Nm @1500 rpm                                | 467                | 490                | 540      |
| Rated engine speed                                     |   | 2200               | 2200               | 2200     |
| <b>Engine</b>  |   |                    |                    |          |
| Engine type / no. of Cylinders / Capacity / Aspiration | AGCO POWER AP44 / 4 / 4400cc / Turbocharged |                    |                    |          |
| <b>Transmission type</b>                               |   |                    |                    |          |
| 12 x 12 Side shift                                     | ●   | ●                  | ●                  |          |
| <b>Power take-off</b>                                  |   |                    |                    |          |
| IPTO single speed - 540 rpm                            | ●   | ●                  | ●                  |          |
| <b>Steering</b>  |   |                    |                    |          |
| Hydrostatic  | ●   | ●                  | ●                  |          |
| <b>Hydraulics</b>                                      |   |                    |                    |          |
| 3-point linkage control                                | Lever operated ELC                          | Lever operated ELC | Lever operated ELC |          |
| Lift capacity  | Max Kg                                      | 5200               | 5200               | 5200     |
| Standard hydraulic pump capacity                       | Litre/min                                   | 57                 | 57                 | 57       |
| Optional hydraulic pump capacity                       | Litre/min                                   | 98                 | 98                 | 98       |
| System Pressure  | bar   | 200                | 200                | 200      |
| <b>Spool valves</b>                                    |   |                    |                    |          |
| 2 x DA / KO / FL                                       | ●   | ●                  | ●                  |          |
| <b>Brakes</b>  |   |                    |                    |          |
| Type   | Oil immersed                                | Oil immersed       | Oil immersed       |          |
| <b>Standard wheels and tyres</b>                       |   |                    |                    |          |
| Front  | 380/85 R24                                  | 380/85 R24         | 380/85 R24         |          |
| Rear   | 460/85 R38                                  | 460/85 R38         | 460/85 R38         |          |
| <b>Weights and Dimensions</b>                          |   |                    |                    |          |
| Weight without ballast - Non-cab                       | Kg  | 4000               | 4000               | 4000     |
| Length   | mm  | 4925               | 4925               | 4925     |
| Height with ROPS / Canopy                              | mm  | 2740               | 2740               | 2740     |
| Wheelbase  | mm  | 2500               | 2500               | 2500     |
| <b>Capacities</b>                                      |   |                    |                    |          |
| Fuel tank  | Litres                                      | 170                | 170                | 170      |

● Standard

# MF 6700

- 3 NEW models, 112 hp to 132 hp from AGCO POWER four cylinder engines
- All new 12x12 synchronised transmission in two ranges
- 4 WD

## Key features

- ROPS and canopy
- 57 l/min hydraulic pump flow standard with 98 l/min optional
- 2 spool valves standard
- 540 rpm independent PTO
- Flat floor platform operator station



For even greater productivity a range of optional equipment is available. For full details please consult your local Massey Ferguson dealer.

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.