

112-132hp (83-98kW)



Specifications

Engine Performance
Engine Power
Max Torque
Rated engine speed
Engine
Engine type / no. of Cylinders /Capacity / Aspiration
Transmission type
16 x 16 Dyna-4 Semi-powershift
32 X 32 Dyna-4 with Supercreep
PowerShuttle
Power take-off
IPTO 540 / 540e / 1000 rpm
Front axle
Туре
Steering
Hydrostatic
Hydraulics
Туре
Oil flow
Pressure
3-point linkage contol
Lift capacity
Spool valves
2 x DA KO FL ZL FD
3 x DA KO FL ZL FD
Brakes
Туре
Standard wheels and tyres
Front
Rear
Operator environment
Туре
Weights and Dimensions
Weight without ballast
Length
Height
Wheelbase
Capacity
Fuel Tank

	MF 6711R	MF 6712R	MF 6713R	
SO hp (kW)	112 (83)	122 (91)	132 (98)	
Nm @1500 rpm	460	510	540	
		2200		
	AGCO Power AP44 / 4 / 4400cc / Turbocharged			
		•		
	0			
		•		
		•		
		4WD with Hydrolock		
		•		
		CCLS		
Litre/min	110			
bar	200			
	ELC			
max kgf	5200			
		•		
		0		
		Oil immersed		
		On minorood		
		380/85R28		
	460/85R38			
	Cab with air conditioning			
kg		5000		
mm	4851			
mm	2885			
mm - 4WD	2626			
		2320		
Litres		210		



MF 6700R

- 3 NEW Models 112 132hp (83 - 98kW) from AGCO Power **four Cylinder Engines**
- Dyna-4 16 x 16 Semi-powershift **Transmission**
- Heavy Duty 4WD Front Axle

Key features

- 110 I/min CCLS Hydraulic System
- 5200kg Lift Capacity with ELC
- 2 Auxiliary Hydraulic Valves
- 3 Speed IPTO 540 / 540e / 1000 revs/min
- Flat Floor Cab with Air Conditioning
- Auto Guide Option



For even greater productivity a range of optional equipment is available. For full details please consult your local Massey Ferguson dealer.

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.