

UNI & AGRI GRADER



Features

- Weighted Blade Box
- Ballasted Wheel Arms
- Reversible Cutting Edges
- Hydraulic Lift and Tilt
- Two-Lever Hydraulic Control Valve
- Mechanical Blade Angling
- Off-Centre Operation

Specifications

MODEL	RGR100	RGR150
BLADE WIDTH (mm/inch)	2400 (94-1/2)	3000 (118-1/8)
TRANSPORT WIDTH (mm/inch)	1697 (66-13/16)	2121 (83-1/2)
LENGTH (mm/inch)	5839 (229-15/16)	6933 (272-15/16)
TRANSPORT LENGTH (mm/inch)	4092 (161-1/8)	4812 (189-7/16)
WORKING HEIGHT (mm/inch)	992 (39-1/16)	1050 (41-3/8)
WEIGHT (kg/lbs)	1000 (2205)	1500 (3307)
WHEELS	2 X 6.00 X 16.0	2 X 7.50 X 16.0
HITCH (cat.)	TRAILED (CAT 2)	TRAILED (CAT 3)
BLADE ANGLE	0° - 45°	0° - 45°
RECOMMENDED POWER REQUIREMENT (kw/hp)	52 (70)	67 (90)

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919
John (National) +27 83 660 1275 • Jairus (Spares) +27 79 690 4546

30 3rd Street, Babelegi, Temba, North West, South Africa, 0407
Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400
T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

www.radium.co.za

