

BULKSPREAD



Features

- High-Quality Painted Mild Steel Bin and Chassis Construction is a welded construction made of sheet metal and plate. The chassis is constructed of high-grade tubing to offer additional strength and flex.
- Hitch Safety Chain in case the hitch, hitch bolts or tractor drawbar break.
- A Robust Parking Jack for easy hitching and detachment of the machine.
- S-design Drawbar for a sharper turning circle ensuring greater, more streamlined movability
- High floatation wheels to improve tracking and reduce compaction
- Durable Imported Axles of the highest quality and conform to CE and or European standards.
- Detachable Axles allowing the customer to bolt different size axles on and off.
- Integrated Grid

Pick Your Extras

- 3CR12 Bin Construction
- 304 Stainless Steel Bin Construction
- Stand-alone Hydraulic Power Pack (PTO)
- Rear Belt Attachment
- Single Channel Isobus Kit
- Dual Channel Isobus Kit
- Camera Package
- Flood Light Package
- Road Light Package
- Tarpaulin Kit
- Weighing System Kit

Specifications

MODEL	RSP100-11.0G	RSP100-11.0H	RSP100-13.0G	RSP100-13.0H
LOAD CAPACITY (kg/lbs)	11000 (24251)	11000 (24251)	13000 (28660)	13000 (28660)
CAPACITY (m ³ /ft ³)	8 (283)	8 (283)	10 (353)	10 (353)
EMPTY WEIGHT (kg/lbs)	2600 (5732)	2600 (5732)	2850 (6283)	2850 (6283)
REQ. OIL FLOW (l/min/gal/min)	50 (13.2)	110 (29)	50 (13.2)	110 (29)
3 SPEED GROUND RELATED GEARBOX	•	•	•	•
HYDRAULIC DRIVE GEARBOX	•	22:01	•	22:01
AXLE (mm/inch)	90 (3-1/2)	90 (3-1/2)	100 (3-15/16)	100 (3-15/16)
WHEELS	2 x 560/60 R 22.5	2 x 560/60 R 22.5	2 x 600/55 R 26.5	2 x 600/55 R 26.5
TRACTOR POWER REQUIREMENT (kw/hp)	105 (140)	105 (140)	135 (180)	135 (180)
A - OVERALL LENGTH (mm/inch)	6490 (255-1/2)	6490 (255-1/2)	7011 (276)	7011 (276)
B - DRAWBAR LENGTH (mm/inch)	1948 (76-11/16)	1948 (76-11/16)	1948 (76-11/16)	1948 (76-11/16)
C - BIN LENGTH (mm/inch)	3606 (141-15/16)	3606 (141-15/16)	4206 (165-9/16)	4206 (165-9/16)
D - REAR SECTION LENGTH (mm/inch)	932 (36-11/16)	932 (36-11/16)	932 (36-11/16)	932 (36-11/16)
E - OVERALL WIDTH (mm/inch)	2510 (98-7/8)	2510 (98-7/8)	2660 (104-3/4)	2660 (104-3/4)
F - BIN WIDTH (mm/inch)	2200 (86-5/8)	2200 (86-5/8)	2200 (86-5/8)	2200 (86-5/8)
G - WHEEL CENTRES (mm/inch)	1950 (76-3/4)	1950 (76-3/4)	2050 (80-3/4)	2050 (80-3/4)
H - OVERALL HEIGHT (mm/inch)	2493 (98-3/16)	2493 (98-3/16)	2559 (100-3/4)	2559 (100-3/4)
I - HITCH HEIGHT (mm/inch)	496±50 (19-1/2±2)	496±50 (19-1/2±2)	528±50 (20-3/4±2)	528±50 (20-3/4±2)
J - AXLE HEIGHT (mm/inch)	621 (24-7/16)	621 (24-7/16)	622 (24-7/16)	622 (24-7/16)

• = Not Applicable • = Standard

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919
John (National) +27 83 660 1275 • Jairus (Spares) +27 79 690 4546

30 3rd Street, Babelegi, Temba, North West, South Africa, 0407
Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400
T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

www.radium.co.za

