

ECO RIP



Features

- Compact and Robust Frame Design
- Working Depth 200-450mm
- Wavy Coulter Disc 510X5mm
- Maintenance-Free Bearings On Disc
- Adjustable Depth Control
- Finisher Roller
- CAT 2 or CAT 3 Mounted Hitch
- 150mm Cast Shear

Specifications

MODEL	RER005	RER007
NO. OF SHANKS	5	7
NO. OF DISC	10	14
SHANK SPACING (mm/inch)	500 (15-3/4)	500 (15-3/4)
DISC SPACING (mm/inch)	240 (9-3/8)	240 (9-3/8)
HITCH (cat.)	III NARROW	III NARROW
WORK WIDTH (mm/inch)	2500 (78 -3/4)	3500 (110-1/4)
WIDTH (mm/inch)	2400 (94-1/2)	3200 (126)
LENGTH (mm/inch)	2650 (104-3/8)	2650 (104-3/8)
HEIGHT (mm/inch)	1455 (57-1/4)	1455 (57-1/4)
WEIGHT (kg/lbs)	1200 (2645)	1500 (3306)
TRACTOR POWER REQUIREMENT (kw/hp)	75 (100)	105 (140)

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919
John (National) +27 83 660 1275 • Jairus (Spares) +27 79 690 4546

30 3rd Street, Babelegi, Temba, North West, South Africa, 0407
Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400
T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

www.radium.co.za

