

# CULTIVATORS



## S-TINE TILLER WITH ROLLER



**Standard Roller**



**Easily Transported**



**Three-point Linkage**

This machine is mounted on the tractor's universal three-point linkage system for easy transport. These tillers are secondary soil tillage machines developed for light cultivation, weed control and seedbed preparation. The machines aerate and loosens the upper layer of soil. The optimum working depth is between 50mm to 100mm at a speed of 8 to 12 kilometers per hour. The 2.0m, 2.5m, 3.0m, 3.4m and 4.0m tillers come standard with a roller / crumbler.

STOCK CODE	ASVT 2000	ASVT 2500	ASVT 3000	ASVT 3400	ASVT 4000
NUMBER OF TINES	21	25	31	34	41
TOTAL WIDTH	2 000mm	2 500mm	3 000mm	3 400mm	4 000mm
WORKING DEPTH	50 - 100mm	50 - 100mm	50 - 100mm	50 - 100mm	50 - 100mm
DEPTH CONTROL WHEELS	NO	NO	NO	OPTIONAL	OPTIONAL
WORKING WIDTH	2 000mm	2 500mm	3 000mm	3 400mm	4 000mm
SPACE BETWEEN TINES	100mm	100mm	100mm	100mm	100mm
SWEEP SIZE	100mm	100mm	100mm	100mm	100mm
REQUIRED POWER	35 - 40kW	45 - 50kW	55 - 60kW	65 - 70kW	70 - 75kW
ROLLER / CRUMBLER	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD

*Manufacturer reserves the rights to change the above without any notice.*